

EXPLANATION

ISOPACHS - Showing thickness of coal, in feet. Long dashed where inferred. Isopach interval 1 foot.

STRUCTURE CONTOURS - Drawn on top of coal bed. Long dashed where vertical accuracy possibly not within 40 feet. Contour interval 100 feet (31 m). Datum is mean sea level.

DRILL HOLE - Showing altitude of top of coal bed, and thickness of coal, in feet.


RS-3 - Rock Springs No. 3

COAL BED SYMBOL AND NAME


SUBSURFACE MINING LIMIT - Showing areas where dips of coal beds are greater than 15° and subsurface mining by conventional methods is not considered feasible. Reserve Base tonnages are calculated beyond limit; Reserve tonnages are not. Arrow points toward area where dips are greater than 15°.

TRACE OF FAULT - Bar and ball on down-thrown side when direction of movement is known. Dashed where inferred or approximately located.



To convert feet to meters, multiply feet by 0.3048.



NOTE: Structure contours are not drawn beyond those shown because of insufficient data.



Isopach and structure contour map of the RS-3 coal bed



COAL RESOURCE OCCURRENCE MAP OF THE KANDA QUADRANGLE,
SWEETWATER COUNTY, WYOMING
BY
DAMES & MOORE
1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.